



Reliable Equipments  
Importer & Stockists

## PIPE SCHEDULE CHART

Nominal size [inches]	Outside diameter [inches]	Outside diameter [mm]	Sch-40				Sch-80				Sch-160			
			Wall thickness [inches]	Wall thickness [mm]	Weight [lb/ft]	Weight [kg/m]	Wall thickness [inches]	Wall thickness [mm]	Weight [lb/ft]	Weight [kg/m]	Wall thickness [inches]	Wall thickness [mm]	Weight [lb/ft]	Weight [kg/m]
1/8"	0.405	10.3	0.068	1.73	0.24	0.37	0.095	2.41	0.31	0.47				
1/4"	0.54	13.7	0.088	2.24	0.42	0.84	0.119	3.02	0.54	0.8				
3/8"	0.84	21.3	0.109	2.77	0.85	1.27	0.147	3.73	1.09	1.62	0.188	4.78	1.31	1.95
1/2"	1.05	26.7	0.113	2.87	1.13	1.69	0.154	3.91	1.47	2.2	0.219	5.56	1.94	2.9
1	1.315	33.4	0.133	3.38	1.68	2.5	0.179	4.55	2.17	3.24	0.25	6.35	2.84	4.24
1.25	1.66	42.2	0.14	3.56	2.27	3.39	0.191	4.85	3	4.47	0.25	6.35	3.76	5.61
1.5	1.9	48.3	0.145	3.68	2.72	4.05	0.2	5.08	3.63	5.41	0.281	7.14	4.86	7.25
2	2.375	60.3	0.154	3.91	3.65	5.44	0.218	5.54	5.02	7.48	0.344	8.74	7.46	11.11
2.5	2.875	73	0.203	5.16	5.79	8.63	0.276	7.01	7.66	11.41	0.375	9.53	10.01	14.92
3	3.5	88.9	0.216	5.49	7.58	11.29	0.3	7.62	10.25	15.27	0.438	11.13	14.32	21.35
3.5	4	101.6	0.226	5.74	9.11	13.57	0.318	8.08	12.5	18.63				
4	4.5	114.3	0.237	6.02	10.79	16.07	0.337	8.56	14.98	22.32	0.531	13.49	22.51	33.54
5	5.563	141.3	0.258	6.55	14.62	21.77	0.375	9.53	20.78	30.97	0.625	15.88	32.96	49.11
6	6.625	168.3	0.28	7.11	18.97	28.26	0.432	10.97	28.57	42.56	0.719	18.26	45.35	67.56
8	8.625	219.1	0.322	8.18	28.55	42.55	0.5	12.7	43.39	64.64	0.906	23.01	74.69	111.3
10	10.75	273	0.365	9.27	40.48	60.31	0.594	15.09	64.43	96.01	1.125	28.58	115.6	172.3
12	12.75	323.8	0.406	10.31	53.52	79.73	0.688	17.48	88.63	132.1	1.312	33.32	160.3	238.8
14	14	355.6	0.375	11.13	54.57	94.55	0.75	19.05	106.1	158.1	1.406	35.71	189.1	281.7
16	16	406.4	0.5	12.7	82.77	123.3	0.844	21.44	136.6	203.5	1.594	40.49	245.3	365.4
18	18	457	0.562	14.27	104.7	155.8	0.938	23.83	170.9	254.6	1.781	45.24	308.5	459.4
20	20	508	0.594	15.09	123.1	183.4	1.031	26.19	208.9	311.2	1.969	50.01	379.2	564.8
22											2.125	53.98	451.1	672.3
24	24	610	0.688	17.48	171.3	255.4	1.125	30.96	296.6	442.1	2.344	59.54	542.1	808.2
32	32	813	0.688	17.48	230.1	342.9								